



BO481611
Oven 400 series
Stainless steel-backed full glass door
Width 76 cm
Left-hinged
controls at the top

Handleless door / automatic door opening
Pyrolytic self-cleaning
17 heating methods, with core temperature probe, rotisserie spit and baking stone function
TFT touch display
Panel-free appliance with surface control module
Electronic precision temperature control from 85° F - 570° F.
4,5 cu.ft. net volume
Energy efficiency class A

Heating methods
 Hot air.
 Eco hot air.
 Top + bottom heat.
 Top + 1/3 bottom heat.
 Top heat.
 1/3 top + bottom heat.
 Bottom heat.
 Hot air + bottom heat.
 Hot air + 1/3 bottom heat.
 Full surface grill + circulated air.
 Full surface grill.
 Compact grill.
 Baking stone function.
 Roaster function.
 Dough proofing.
 Defrosting.
 Keeping warm.

Operation
 Automatic door opening.
 Rotary knob and TFT touch display operation.
 Clear text display in 25 languages.
 Option to save individual recipes (incl. core temperature probe).
 Information key with use indications.
 Side-opening door opens up to 180° angle.

Features
 Core temperature probe with automatic shut-off.
 Rotisserie spit.
 Baking stone outlet.
 Actual temperature display.
 Rapid heating.
 Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
 60 W halogen top light.
 2 x 10 W halogen light on the side.
 Enamelled side shelf supports with 5 tray levels, pyrolysis-safe.

Safety
 Thermally insulated door with four-fold glazing.
 Child lock.
 Safety shut-off.
 Cooled housing with temperature protection.

Cleaning
 Pyrolytic self-cleaning.
 Gaggenau Clean-Enamel.
 Heated air cleaning catalyser.

Planning notes
 Door hinge not reversible.
 The front of the appliance extends 1 7/8" from the cabinet front.
 If the handle (optional accessory) is retrofitted, the outer edge of the door handle extends 3 11/16" (94 mm) from the furniture cavity.

Product Features
Cooking mode
 Baking stone function, Bottom heat, Bottom heating, 1/3 top heat., Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot air and 1/1 bottom heating, Hot air and 1/3 bottom heating, Hot Air-Eco, Hot air grilling, Roaster function, Top heat, Top heating, 1/3 bottom heat., warming
Integrated Cleaning system
 Self Clean
Interior Lights - cavity 1
 3
Pull-out system
 Accessory
Timer settings
 Alarm, Off, On, timer
Included accessories
 1 x enamel baking tray, suit. pyrolytic clean, 1 x rotary spit, 1 x grill shelf, 1 x grill tub with grid, 1 x pluggable meat probe
Bake Element Wattages cavity 1 (W)
 1700
Broil Element Wattages cavity 1 (W)
 3900
Convection Element Wattages cavity 1 (W)
 1900
Microwave Wattages (W)
Drawer wattage (W)

Consumption and connection features
UPC code
 825225911173
Product color
 Stainless steel
Alternative colors available

Energy source
 Electric
Watts (W)
 5520
Current (A)
 25
Volts (V)
 208/220-240
Frequency (Hz)
 60
Approval certificates
 ETL
Power cord length (in)
 47 1/4
Power cord length (cm)
 120
Plug type
 fixed connection

Required cutout size (HxWxD) (in)
 26 3/16 " x 28 1/2 " x 21 11/16 "
Required cutout size (HxWxD) (mm)
 665 x 724 x 550
Overall appliance dimensions (HxWxD) (mm)
 670 x 752 x 547
Product packaging dimensions (HxWxD) (in)
 33 7/8 x 33 7/16 x 29 15/16
Net weight (lbs)
 175
Net weight (kg)
 79.0
Gross weight (lbs)
 189
Gross weight (kg)
 86.0

2016-07-12
 Page 1

Consider the overhang, incl. the door handle where applicable, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 90° door opening angle.

To achieve the 21 5/8" installation depth, the connecting cable needs to follow the slanted edge on the lower right hand corner of the housing. The mains socket needs to be planned outside of the built-in niche.

Rating
 Energy efficiency class A.
 Total rating 5.5 kW.
 Total Amps: 25 A
 208 / 220 - 240 V / 60 Hz
 Connecting cable 47 1/4 (1.2 m) without plug.

Color Variants
BO481611
Stainless steel-backed full glass door
Width 76 cm

Included accessories
 1 x enamel baking tray, suit. pyrolytic clean.
 1 x rotary spit.
 1 x grill shelf.
 1 x grill tub with grid.
 1 x pluggable meat probe.

Optional accessories
BA018105
Pull-out system
BA028115
Baking tray, enameled
BA038105
Wire rack, chromium-plated
BA058115
Heating element for baking stone and cast-iron roaster
BA058133
Baking stone
BS020002
Pizza peel, additional set of 2
GN340230
Non-stick aluminum cast-iron roaster

Product Variants
BO480611
Oven 400 series
Stainless steel-backed full glass door
Width 76 cm
Right-hinged
controls at the top

