



#### Color Variants

**BX481611**  
Stainless steel-backed full glass door  
Width 76 cm

#### Included accessories

2 x enamel baking tray, suit. pyrolytic clean.  
1 x rotary spit.  
2 x grill shelf.  
2 x grill tub with grid.  
1 x pluggable meat probe.

#### Optional accessories

**BA018105**  
Pull-out system  
**BA028115**  
Baking tray, enameled  
**BA038105**  
Wire rack, chromium-plated  
**BA058115**  
Heating element for baking stone and cast-iron roaster  
**BA058133**  
Baking stone  
**BS020002**  
Pizza peel, additional set of 2  
**GN340230**  
Non-stick aluminum cast-iron roaster

#### Product Variants

**BX480611**  
Double oven 400 series  
Stainless steel-backed full glass door  
Width 76 cm  
Right-hinged  
Controls centered

**BX481611**  
Double oven 400 series  
Stainless steel-backed full glass door  
Width 76 cm  
Left-hinged  
Controls centered

**Pyrolytic self-cleaning**  
17 heating methods, with core temperature probe, rotisserie spit and baking stone function  
TFT touch display  
Electronic precision temperature control from 85° F - 570° F.  
2x 4.5 cu. ft. net volume  
Energy efficiency class A

#### Heating methods

Hot air.  
Eco hot air.  
Top + bottom heat.  
Top + 1/3 bottom heat.  
Top heat.  
1/3 top + bottom heat.  
Bottom heat.  
Hot air + bottom heat.  
Hot air + 1/3 bottom heat.  
Full surface grill + circulated air.  
Full surface grill.  
Compact grill.  
Baking stone function.  
Roaster function.  
Dough proofing.  
Defrosting.  
Keeping warm.

#### Operation

Rotary knob and TFT touch display operation.  
Clear text display in 25 languages.  
Information key with use indications.  
Side-opening door opens up to 180° angle.

#### Features

Meat probe with automatic shut off (lower oven).  
Rotisserie spit (lower oven).  
Baking stone outlet.  
Actual temperature display.  
Rapid heating.  
Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.  
60 W halogen top light.  
10 W halogen light on the side.  
Enamelled side shelf supports with 5 tray levels, pyrolysis-safe.

#### Safety

Thermally insulated door with four-fold glazing.  
Child lock.  
Safety shut-off.  
Cooled housing with temperature protection.

#### Cleaning

Pyrolytic self-cleaning.  
Gaggenau Clean-Enamel.  
Heated air cleaning catalyser.

#### Planning notes

Door hinge not reversible.  
The front of the appliance extends 1 7/8" from the cabinet front.  
The outer edge of the door handle extends 3 11/16" (94 mm) from the furniture cavity.  
Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.  
When planning a corner solution, pay attention to the 90° door opening angle.  
To achieve the 21 5/8" installation depth, the connecting cable needs to follow the slanted edge on the lower right hand corner of the housing.

#### Product Features

##### Cooking mode

Baking stone function, Bottom heat, Bottom heating, 1/3 top heat., Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot air and 1/1 bottom heating, Hot air and 1/3 bottom heating, Hot Air-Eco, Hot air grilling, Roaster function, Top heat, Top heating, 1/3 bottom heat., warming

##### Cooking method second cavity

Baking stone function, Bottom heating, Bottom heating, 1/3 top heat., Defrosting, Dough proving setting, Hot air, Hot air and 1/1 bottom heating, Hot air and 1/3 bottom heating, Hot Air-Eco, Hot air grill, Large-area grill, Roaster function, Small area grill, Top/bottom heating, Top heating, Top heating, 1/3 bottom heat., Warming

##### Integrated Cleaning system

No, Self Clean

##### Number of interior lights

2

##### Included accessories

2 x enamel baking tray, suit. pyrolytic clean, 1 x rotary spit, 2 x grill shelf, 2 x grill tub with grid, 1 x pluggable meat probe

##### Bake Element Wattages cavity 1 (W)

1700

##### Broil Element Wattages cavity 1 (W)

3900

##### Convection Element Wattages cavity 1 (W)

##### Microwave Wattages (W)

#### Consumption and connection features

##### UPC code

825225911159

##### Product color

Stainless steel

##### Alternative colors available

##### Energy source

Electric

##### Watts (W)

9200

##### Current (A)

40

##### Volts (V)

208/220-240

##### Frequency (Hz)

60

##### Approval certificates

ETL

##### Power cord length (in)

70 7/8"

##### Power cord length (cm)

180

##### Appliance Dimensions (h x w x d) (cm)

142.8 x 75.2 x 54.7

##### Required cutout size (HxWxD) (in)

56 1/8 " x 28 1/2 " x 21 11/16 "

##### Overall appliance dimensions (HxWxD) (in)

56 1/4 " x 29 5/8 " x 21 5/8 "

##### Overall appliance dimensions (HxWxD) (mm)

1428 x 752 x 547

##### Product packaging dimensions (HxWxD) (in)

69.09 x 33.46 x 29.72

##### Net weight (lbs)

336

##### Net weight (kg)

152.0

##### Gross weight (lbs)

380

##### Gross weight (kg)

173.0

##### 2016-07-11

##### Page 1

The mains socket needs to be planned outside of the built-in niche.

#### Rating

Energy efficiency class A.  
Total rating 9.2 kW.  
Total Amps: 40 A  
208 / 220 - 240 V / 60 Hz  
Connecting cable 70 7/8" (1.8 m) without plug.

BX481611  
Double oven 400 series  
Stainless steel-backed full glass door  
Width 76 cm  
Left-hinged  
Controls centered  
2016-07-11  
Page 2

