

3045WC • 45 cm Wine Cellar • Modular 3000 Series







INTEGRATED FRAME

INTEGRATED SOLID





STAINLESS FRAME

STAINLESS SOLID

FEATURES & BENEFITS

PERFORMANCE

INTERIOR/EXTERIOR

INTEGRATION

•	Volume	of	102	litres	holds	un	to	31	wine	bottles	(()	.75	\mathbf{I})

- Temperature range: 3°C 18°C
- Convection cooling system rapidly and efficiently takes items to the set temperature
- U-Select[®] Control offers three distinct modes: Sparkling Wine: 3°C - 10°C, White Wine: 7°C - 12°C, Red Wine: 12°C - 18°C
- U-Select® Control with digital OLED display is conveniently located on upper face of unit
- Relative humidity inside the unit is approx. 50%
- Rubber mounted compressor virtually eliminates vibration

• Black interior is illuminated with LED theatre lighting that automatically turns off when the door is closed, or can be set to stay on for 3, 6, or 24 hours

- Robust full-extension black vinyl coated wine racks allow for easy access and prevent bottles from shifting
- Wine racks accommodate a variety of bottle shapes and sizes; the fourth and fifth racks allow for larger diameter wine and champagne bottles
- LowE coated, argon gas filled triple thermopane glass door provides protection from harmful UV light
- Door swing is field reversible. Unit is shipped with door installed right-hand hinged

To achieve a stainless steel finish, a Euro Style panel accessory must be ordered and installed on an integrated model. Euro Style Panel Accessory must be installed on corresponding unit type (Frame/Solid)

- Robust, concealed and covered hinges with built-in door stop and closer
- Adjustable grille/fascia can be shifted front-to-back and up-and-down
- Grille/fascia can accept a custom integrated plinthe
- Integrated model requires 20 mm custom panel of your choice, or can accept U-Line Euro Style Stainless Steel Panel Accessory (must be ordered separately)
- Four independently adjustable leveling legs; rear legs are adjustable from the front for ease of installation

MODEL DETAILS

Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
U-3045WCINT-00B	220-240 / 50	Field Reversible	Integrated Frame	60 kg
U-3045WCINT-60B	220-240 / 50	Field Reversible	Integrated Solid	58 kg

ACCESSORIES

Model	Description	Finish	Shipping Weight		
U-ESPF45S*	Euro Style Panel Frame 45 cm	Stainless Frame	3 kg		
U-ESP45S*	Euro Style Panel Solid 45 cm	Stainless Solid	4 kg		


^{*}Installs on integrated models.




Modular 3000 Series • 45 cm Wine Cellar • 3045WC

NICHE / RECESS

Dimensions shown apply to Integrated (INT) models with a 20 mm integrated panel/frame installed (applies to U-Line's Euro Stainless Steel Panel Accessory).





PRODUCT FICHE

Model	3045WC		
Category	2		
Energy efficiency class on a scale of A+++ to G	А		
Energy consumption in kWh per year	116 kWh		
Total volume: fridge compartment (net)	N/A		
Total volume: wine compartment (net)	96 L		
Total volume: freezer compartment (net)	N/A		
Frost-free compartment	Yes		
Temperature rise time in event of blackout (hrs)	N/A		
Climate class	ST		
Noise emissions	46 dBA		
Dimensions: width	450 mm		
Dimensions: depth	590 mm		
Dimensions: height	856 mm		
Net weight: solid door	54 kg		
Net weight: glass door	56 kg		
Panel type	Frame Panel (-00 suffix) or Solid Panel (-60 suffix)		
Panel thickness	20 mm		
Panel height	762 mm		
Panel width	445 mm		
Rated frequency	50 Hz		
Rated voltage	220-240 v		
Refrigerant charge	62 g		
Foam blowing agent	HFO-1233zd		
Marine capable	Yes*		

INSTALLATION NOTES

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille/fascia air flow.

For cabinet depths less than 620 mm, electrical socket must be located in the adjacent cabinet or recess in the wall. The power cord length is 180 cm.

This appliance is intended to be used exclusively for the storage of wine.

Please visit U-Line.com to view this model's User Guide. All specifications are subject to change without notice.

COOLING SYSTEM





^{*}Must be installed in a climate controlled environment and operate within the temperatures designated in U-Line's Limited Warranty.